

Name ELLIOTT BOOTS Date 12.11.2012 Truck / City MARTIME Event OFF RD WARS.

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: 1°

UM128 (Std) UMW508 (+2mm High Mount)

Axle Spacer: Out _____ mm In _____ mm

4.8mm Ball Stud Spacer: _____ mm

Wheel Hub: _____ mm

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 1 mm

Toe: In Out 0°

Caster: 25° 30°

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Block position: IN OUT

Axle Height Spacer: 1 mm 1 mm

Front Bulkhead Weight Placement: None Bulkhead Inside _____ oz _____ g On the skid plate _____ oz _____ g * 1oz=28g

Comments: _____

Wheelbase: F: 2 mm R: _____ mm

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____°

Sway Bar: None _____ mm

Camber: 2°

Upper Spacer: 3 mm

Wheelbase: F: 1 mm R: 4 mm

4.8mm Ball Stud: UM129 (Std) UMW508 (+2mm High Mount) 97050M

RR: _____

Mid: _____

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512 RF2 UMW514+UMW515

Wheelbase: F: 2 mm R: 0 mm

Rear Hub add Toe: 0° Type-B (UM519) 0° Type-B2 (UM519-2) 0° Alu (UMW516-0) 0.5° Alu (UMW516-05) 1° Alu (UMW516-1)

Axle Spacer: Out _____ mm In _____ mm

Motor Position: Rear Motor Midship Motor

Diff.: Gear Diff. # _____ Ball Diff.

Comments: _____

Shock

Shock Piston: Front KIT (SHOCK) Rear KIT 5 (HOLE)

Shock Oil: # 40 # 30

Shock Spring: RED (KIT) RED (KIT)

Limiters: in _____ mm out 0 mm in _____ mm out 0 mm

Shock Length(A): KIT mm KIT mm

Shock Length(B): KIT mm KIT mm

Shock Length(C): _____ mm _____ mm

Ball End type: Front: S M L Rear: S M L

Chassis

Screw:

Ride Height: F 18 mm R 18 mm

Battery Position

Battery Type: Straight Separate Short

Battery Placement: Front Rear

Truck Condition

Smooth Sandy Bumpy Soft Dirt Low Truction Grass Med. Truction Blue Groove High Truction Clay Wet Dusty Dry Other

Wing

Blast-S Blast-L Step-S Step-M Step-L Step 2.0

Wing Mount: Narrow Wide

Wing Angle: 4° 7° 10°

Lip: _____

Tire

Front: SCHMAEKER Rear: _____

Inserts: ANWEL ANWEL

Wheel: KYOSHO KYOSHO

Traction Compound: 0 0

Electronics

Motor: LRP X20 7.5

Pinion/Spur: _____

Battery: LRP

ESC: FLOW LRP.

Comment

MINI PINS (WORN) REAR.

STAGGERS FRONT.